

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **KNEAD IT MULTIPURPOSE**

Recommended Use: A two-pack epoxy putty that reshapes, rebuilds and repairs many surfaces.

Supplier: Selleys Australia, a division of DuluxGroup (Australia) Pty Ltd
ABN: 67 000 049 427
Street Address: 1 Gow Street,
 Padstow, NSW 2211
 Australia

Telephone Number: +61 2 9781 8777
Facsimile: +61 2 9781 8825
Emergency Telephone: **1 800 033 111 (ALL HOURS)**

2. HAZARDS IDENTIFICATION

This material is hazardous according to criteria of Safe Work Australia; HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Risk Phrases: Irritating to eyes and skin. May cause sensitisation by skin contact.

Safety Phrases: Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water (or soap and water if product is water insoluble). Wear suitable protective clothing, gloves and eye/face protection.

Poisons Schedule: None allocated.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Bisphenol A-Epichlorhydrin reaction product(NAMW<700)	25068-38-6	10-<30%	R36/38 R43 R51/53
Crystalline silica (Quartz)	14808-60-7	10-<30%	R48/20, Carc. Cat. 1 R49
2,4,6-Tri(dimethylaminomethyl)phenol	90-72-2	1-<10%	R22,R36/38
Zinc sulphide	1314-98-3	1-<10%	-
Ingredients determined not to be hazardous	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:
Not applicable.

Skin Contact:
If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Safety Data Sheet

**Eye Contact:**

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

Medical attention and special treatment:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazards from combustion products:

Combustible solid. On burning will emit toxic fumes, including those of oxides of carbon , oxides of nitrogen and oxides of sulfur .

Precautions for fire fighters and special protective equipment:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

Methods and materials for containment and clean up:

Wear protective equipment to prevent skin and eye contact. Scrape up excess material before cure. Collect and seal in properly labelled containers or drums for disposal. Cured material can only be removed by cutting or abrasion.

7. HANDLING AND STORAGE

Conditions for safe storage:

Store in cool place and out of direct sunlight. Store away from foodstuffs. Keep containers closed when not in use - check regularly for spills.

Precautions for safe handling:

Avoid skin and eye contact.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits: No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

Silica Crystalline - Quartz: 8hr TWA = 0.1 mg/m³

Safety Data Sheet



As published by the National Occupational Health and Safety Commission.

No Exposure Standards assigned to other constituents.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering controls:

Use in well ventilated areas. Keep containers closed when not in use.

Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Green



MANUFACTURE, PACKAGING AND TRANSPORT: Green - Wear overalls (or 'issued' long pants and long sleeve tops), safety boots, gloves and safety glasses. Always wash hands before smoking, eating, drinking or using the toilet. Avoid breathing dust when sanding. Wet sand or use a dust mask.

FOR CONSUMER USE: Avoid contact with eyes and skin. Wash hands after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Putty
Colour:	White
Odour:	Sulfur , Mercaptan
Solubility:	Insoluble in water.
Specific Gravity:	1.95 @20°C
Relative Vapour Density (air=1):	Not applicable
Vapour Pressure (20 °C):	Not applicable
Flash Point (°C):	Not applicable
Flammability Limits (%):	Not applicable
Autoignition Temperature (°C):	Not applicable
% Volatile by Volume:	<1
Solubility in water (g/L):	Insoluble
Melting Point/Range (°C):	Not available
Boiling Point/Range (°C):	Not applicable
Decomposition Point (°C):	Not available
pH:	Not applicable
Viscosity:	Not applicable
Evaporation Rate:	Not applicable

10. STABILITY AND REACTIVITY

Chemical stability:	Stable under normal conditions of use.
Conditions to avoid:	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame.
Incompatible materials:	Incompatible with oxidising agents.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur.
Hazardous reactions:	Hazardous polymerisation will not occur.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting, diarrhoea, and abdominal pain.
Eye contact:	An eye irritant.
Skin contact:	Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
Inhalation:	Not expected to cause respiratory irritation.

Long Term Effects:

No information available for the product. Repeated or prolonged breathing of crystalline silica dust may result in chronic lung diseases such as silicosis. However, due to the physical state of this product this is not relevant unless it is sanded, abraded or crushed. In such cases, precautions should be taken to avoid the breathing of dust.

Toxicological Data: No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
--------------------	--------------------------------

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Product Name: KNEAD IT MULTIPURPOSE
Substance No: 000704326301

Issued: 01/05/2012
Version: 4

Safety Data Sheet



Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification: This material is hazardous according to criteria of Safe Work Australia; HAZARDOUS SUBSTANCE.

Hazard Category: Xi: Irritant

Risk Phrase(s): R36/38: Irritating to eyes and skin.
R43: May cause sensitisation by skin contact.

Safety Phrase(s): S24/25: Avoid contact with skin and eyes.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S28: After contact with skin, wash immediately with plenty of soap and water.
S36/39: Wear suitable protective clothing and eye/face protection.

Poisons Schedule: None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

For further copies of this sheet or other product information contact Selleys Customer Service.

Phone: 1300 555 205 (Australia wide)
Fax: 1300 555 305 (Australia wide)
Phone: 0800 735 539 (New Zealand)
Fax: 0800 804 583 (New Zealand)

Reason(s) for Issue:
5 Yearly Revised Primary SDS
Alignment to HSNO requirements

This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.