



IF IT'S SELLEYS IT WORKS™

Technical Data Sheet

No More Gaps Multipurpose

Updated
11/10/2010

DESCRIPTION

No More Gaps Multipurpose is a flexible gap filler specially formulated to withstand expansion and contraction which can cause rigid fillers or other less flexible gap sealants to crack and fall out. Its smooth finish and superior flexibility make it perfect for hiding unsightly gaps.

SIZES AVAILABLE

Available in both white and light brown in 475g cartridge. 450g tube. Grey only.

USES

No More Gaps Multipurpose may be used for sealing gaps and joints where some movement is anticipated.

- Between window or door frames and the wall.
- Along skirting boards and around cornices.
- Between bench tops and tiles.
- In corners or between walls and ceilings, or where shrinkage or movement has caused rigid fillers to crack.

TECHNICAL FEATURES

- Excellent adhesion - to brick, concrete, timber, fibre cement sheeting, glass, particle boards, plasterboard, aluminium, paint and ceramics tiles.
- Superior flexibility and stretch capability – to cope with building movement.
- Maximum durability – long term resistance to cracking and crumbling
- Paintable - can be painted with most paints after the surface has skinned (approx. 30 minutes. See note under 'HOW TO USE')
- Sag resistant
- Non-staining - WILL NOT stain building materials.
- Good resistance to weathering
- Interior & Exterior use
- Water clean up

TECHNICAL DETAILS

Property	Typical Result
Tack Free Time (@ 25°C and 50% R.H.):	40 minutes (longer at low temperatures and high humidities)
Skin Time (@ 25°C and 50% R.H.):	20 minutes (longer at low temperatures and high humidities)
Flow/Sag/Slump (Mil-S-8802E):	Less than 2mm.
Shore A Hardness – Cured sealant	Greater than 40
Ultimate Tensile Strength(ASTM D412):	0.6 MPa
Maximum elongation (ASTM D412):	Up to +300%
Peel Strength (Anodised Al):	5 Kgcm-1:
Heat Resistance	Bonds will resist temporary exposure to temperatures up to 140 °C
Joint Movement Capability (ISO 9046):	Up to ± 20 % of joint width (expansion joints where depth is not greater than half joint width).

LIMITATIONS

- Maximum gap size recommended: width 25mm, depth 12mm.
- NOT for gaps between tongue and groove boards or weatherboard overlaps. Use No More Gaps Weatherboard.
- Not for sealing around bathtubs, kitchen sinks and in shower recesses. Use Selleys Wet Area Silicone sealant.
- Not suitable where excessive joint movement occurs or for areas of frequent water immersion - use the appropriate Selleys Silicone Sealant or Selleys Pro Series Polyurethane Sealant.
- Not to be applied at temperatures below 5° C



Ph: AU - 1300 555 205
Ph: NZ - 0800 735 539
Website - www.selleys.com.au
Email - selleys.customer.service@selleys.com.au
Head Office: 1 Gow Street, Padstow NSW 2211 AU

Page | 1

© 2009-2012 Selleys Pty Limited
ABN 67 000 049 427

All information contained in this Product Information Sheet is as accurate and up-to-date as possible. Products can be expected to perform as indicated in this Sheet, so long as application procedures are followed as recommended. However, there are no expressed or implied warranties set out in this information other than those implied by Commonwealth, State or Territory Legislation.



IF IT'S SELLEYS IT WORKS™

Technical Data Sheet

No More Gaps Multipurpose

Updated
15/05/2012

HOW TO USE

- Surfaces to be caulked must be thoroughly clean and free from dust, grease, flaking paint and old or crumbling caulk. Remove soap residue from tiles using a brush or detergent and then rinse off with water. Other surfaces can be cleaned with acetone to remove grease residues.
- Extrude a bead of product with a steady pressure, forcing caulk into the crack.
- Smooth with a wet finger or spatula.
- Allow surface to skin firmly before painting. If oil based paints are to be used or if gaps are large, allow sealant to set for 48 hours before painting.

Note: Paints that shrink during drying may crack, e.g. some water-based undercoats and flat paints. To test, paint a small section of sealant.

Paint cracking may be reduced by first:

- Painting the sealant with acrylic semi-gloss paint or oil-based undercoat, or,
- Allowing sealant to cure thoroughly before painting.

CLEAN-UP

Clean up excess caulk with water (a damp cloth) before it dries. Cured caulk will need to be cut away and remaining caulk can be softened with acetone and then removed.

No More Gaps Multipurpose will typically skin after approx. 30 minutes and cure within 48 hours to a durable, flexible seal. Allow for longer skin and cure times under cold/damp conditions or for larger gaps.

Product should be protected from exposure to rain (water) until firmly skinned.

WARNINGS/FIRST AID & SHIPPING INFORMATION: Refer to the **MSDS** section located on the Selleys Website.



Ph: AU - 1300 555 205

Ph: NZ - 0800 735 539

Website - www.selleys.com.au

Email - selleys.customer.service@selleys.com.au

Head Office: 1 Gow Street. Padstow NSW 2211 AU

Page | 2

© 2009-2012 Selleys Pty Limited
ABN 67 000 049 427

All information contained in this Product Information Sheet is as accurate and up-to-date as possible. Products can be expected to perform as indicated in this Sheet, so long as application procedures are followed as recommended. However, there are no expressed or implied warranties set out in this information other than those implied by Commonwealth, State or Territory Legislation.