

## Selleys No More Gaps

### Description

SELLEYS No More Gaps is a general-purpose interior/ exterior flexible gap filler. Its water based formulation delivers superior flexibility & long term resistance to cracking & crumbling, giving you a lasting finish.

### Product Information

Packaging	Size	Colour
Tube	150 g	White

### Uses

Suitable for use on walls, plasterboard, wood, particle board, cement sheeting, aluminium and glass.

- Between window or door frames and the wall.
- Along skirting boards and around cornices.
- Between bench tops and tiles.
- In corners or between walls and ceilings, or where shrinkage or movement has caused rigid fillers to crack.

### Features

- Superior Flexibility
- Weatherproof
- Sag Resistant
- Paintable
- Low Odour

### Technical Details

Property	Typical Result
<b>Technology</b>	Water-based
<b>Colour</b>	White
<b>Sag Resistance</b>	≤3 mm
<b>Skin Time (23°C, 50% Humidity)</b>	≤ 1 h
<b>Peel Strength (Anodised Aluminium,)</b>	≥0.25 MPa
<b>Shore A Hardness (Cured sealant)</b>	≥20 - 90
<b>Elongation at Break (ASTM D412)</b>	≥100%
<b>Modulus at 100% Elongation (ASTM D412)</b>	0.35 MPa
<b>Extrusion Rate</b>	≥100 mL/min
<b>Shelf Life (un-opened cartridge)</b>	24 Months
Indicative data only, not intended for preparation of specifications	

### Directions for Use

1. Ensure surfaces are clean, dry and free from dust or grease.
2. Cut nozzle at 45° angle, cut cartridge tip and fit nozzle. Insert cartridge into caulking gun.
3. Apply with caulking gun, pushing product into gap or joint.
4. To achieve a better finish, apply masking tape on both sides of the joint before caulking. After smoothing the caulk, immediately remove the tape to prevent the sealant from contaminating the substrate, and then wait for the sealant to cure.
5. Smooth with a wet gloved finger/spatula.
6. Clean up:  
Wet – Clean up using a damp cloth.  
Dry – Clean up using scraper.
7. Allow surface to skin prior to painting (approx. 1 h\*) For larger gaps, it is recommended to apply the sealant in two passes: first, fill the gap with one layer of sealant and allow it to dry, then apply a second layer to level it. After waiting 48 hours for the sealant to dry, you can proceed with painting. (The drying time of the sealant may vary depending on weather, application method, and environmental conditions).

### Storage

For maximum shelf life, the product should be kept sealed and in a cool, place out of direct sunlight. Store product above 5 °C

### Limitations

- The construction environment must be well-ventilated (before the sealant dries, avoid direct wind blowing on it).
- The optimal ratio of joint width to depth is 2:1.
- Do not use in areas with significant joint movement or noticeable vibration.
- Do not apply directly on loose or highly absorbent substrates (such as putty or gypsum; proper sealing and reinforcement must be done before caulking).
- Do not use in areas exposed to long-term moisture or submerged in water.
- Application is not recommended in environments below 5 °C.
- Before the sealant is fully cured, ensure proper waterproof protection and rain protection.

### Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – [www.selleys.com](http://www.selleys.com)