

Selleys No More Gaps

Description

Selleys No More Gaps is a general-purpose interior / exterior multipurpose flexible gap filler. Its water based formulation delivers superior flexibility & long term resistance to cracking & crumbling, giving you a lasting finish.

Product Information

Packaging	Size	Colour
Tube	150g	White
Cartridge	475g	White
Cartridge	475g	Grey
Cartridge	475g	Light Brown
Cartridge	475g	Cotton White
Cartridge	475g	Cream
Cartridge	475g	Black
Cartridge	475g	Cedar
Cartridge	475g	Charcoal
Cartridge	475g	Terracotta
Cartridge	475g	Baked Earth
Cartridge	475g	Brown
Cartridge	475g	Ivory
Cartridge	475g	Coffee
Cartridge	475g	Light Grey
Cartridge	475g	Vallina

Uses

Suitable for use on plasterboard, wood, particle board, cement sheeting, aluminium and glass.

Features

- Long Lasting
- High Flexibility
- Paintable
- Low Shrink

Technical Details

Property	Typical Result
Technology	Water-based
Colour	White

Density	1.64
Sag	0 mm
Skin Time (23°C, 50%RH)	30 minutes
Shore A Hardness (Cured sealant)	45
Elongation at Break (ISO 37)	400%
Tensile Strength (ISO 37)	1.3 MPa
Movement Capability (ISO 9046)	Up to 15%
Indicative data only, not intended for preparation of specifications	

Directions for Use

1. Ensure surfaces are clean, dry and free from dust or grease.
2. Cut nozzle at 45° angle, cut cartridge tip and fit nozzle. Insert cartridge into caulking gun.
3. Apply with caulking gun, pushing product into gap or joint.
4. Smooth with a wet gloved finger/spatula.
5. Clean up: Wet – Clean up using a damp cloth. Dry – Clean up using scraper.
6. Allow surface to skin prior to painting (approx. 30 minutes*)

Tips

*To avoid paint cracking apply to gaps (no larger than 5mm deep and 10 mm wide) at a temperature above 10°C. Allow sealant to dry before painting over. Avoid applying paint too thickly. Allow 24-48 hours before painting with oil based paints. Longer drying times are required for flat and ceiling paints because they are highly filled (i.e. contains lower binder content than other paints.) This means the paint does not flex as much when the sealant dries.

Coverage

One cartridge will produce a 6mm bead of sealant approximately 8.3 metres long.

Storage

Store unopened products between 5°C-30°C in a cool dry place away from direct sunlight. Unopened products can be stored for 24 months from the date of manufacture.

Selleys No More Gaps

Limitations

- Do not apply while temperature is below 5°C, or if it is raining.
- Not suitable for permanent water immersion or in constantly damp areas.
- Not suitable for gaps between tongue and groove boards or weatherboards.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com