

## Selleys Kwik Grip (Shoe Adhesive)

### Description

SELLEYS Kwik Grip (Shoe Adhesive) is a heat & water resistant, solvent based, flexible contact adhesive for repairing shoes, handbags and luggage.

### Product Information

Packaging	Size	Colour
Tube	15 mL	Light Brown
Tube	50 mL	Light Brown

### Uses

Kwik Grip Contact adhesive is suitable for use on a wide variety of surfaces its contact bond achieves instant adhesion on a wide range of surfaces. It is great for bonding cork, rubber, leather, canvas, laminated plastics\*, felt, metals and timber.

### Features

- Instant bond
- Heat resistant
- Flexible
- Interior and Exterior

### Technical Details

Property	Typical Result
Technology	Solvent-based
Colour	Light Brown
Density	0.79
Application Temperature	10 °C to 40 °C
Peel Strength ASTM D903 (per 25mm)	Minimum 150 N
Service Temperature	-10 °C to 60 °C

Indicative data only, not intended for preparation of specifications

### Surface Preparation

Ensure surfaces to be bonded are clean, dry and free from grease and dirt.

### Directions for Use

Use in a well-ventilated area.

#### Contact Bond

- If cutting material to size, ensure material is slightly oversize all around and trim once bonded.
- Using applicator completely cover both surfaces with Kwik Grip and keep apart until adhesive is 'touch dry'. - approx 20 minutes, no more than 40 minutes.
- Carefully position items, keeping apart with dowels, when edges are perfectly aligned, remove dowels and working from one edge press surfaces firmly together. Grabs immediately on contact.
- Secure the bond by running a roller over the bonded surfaces or by hammering the surfaces from the centre outwards using a padded block. Maximum strength is reached after 24 hours.

#### Wet Bonding

Apply Kwik Grip to one surface, then bring surfaces together and clamp until dry.

#### Clean Up

Clean up with mineral turps while wet. Once dried adhesive is difficult to remove.

#### Storage

Store in dry and cool place with temperature below 30 °C.

#### Limitations

- Do not apply below 10 °C.
- Will not bond to Polypropylene or Polyethylene.
- \*Some plastics such as vinyl sheeting and polystyrene are attacked by Kwik Grip. Test in an inconspicuous area prior to application. Seek advice of vinyl flooring manufacturers prior to use with their products as discoloration and bubbling can occur with some types. A water-based adhesive such as Kwik Grip Advanced is generally more suitable.
- Not suitable for bonding rough, ill-fitting surfaces. (Consider the suitability of alternative products such as Liquid Nails or Liquid Nails Fast for these applications)

#### Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – [www.selleys.com](http://www.selleys.com)