

Plastic Wood

Description

Plastic Wood is a fast-setting solvent based interior wood filling cement suitable for all types of woodwork.

Product Information

Packaging	Size	Colour
Tube	50g	Maple
Tin	230g	Maple

Uses

Selleys Plastic Wood is ideal for filling holes, dents and chips in natural wood.

Features

- Can be sanded, nailed, planed, painted, or lacquered.
- Sets to a hard finish.
- Can be treated in all respects as real wood by staining, varnishing, or painting.
- Fills holes up to 6mm deep, fully cures within 24hrs*, depending on gap size and environment.

Technical Details

Property	Typical Result
Technology	Solvent based
Colour	Maple
Density	0.94
Drying time	<24hrs*
Indicative data only, not intended for preparation of specifications	

Surface Preparation

Surface must be clean, dry and free from loose material.

Directions for Use

1. Surface must be clean, dry and free from loose material.
2. For tin, stir content thoroughly
3. Apply with a putty knife. Slightly overfill deep holes to allow for sanding. Do not fill more than 6mm in each application.
4. Allow to dry before sanding, staining or painting.
5. Replace lid firmly after use and store in a cool place.

Tips

- Slightly overfill deep holes to allow for sanding.
- Do not fill more than 6mm in each application
- Allow to fully dry before sanding, nailing, or painting.

Clean Up

Clean excess and putty knife with Methylated Spirits

Storage

Store in a cool place away from sunlight and away from any flame or spark source

Limitations

- Plastic Wood is not flexible.
- Not suitable for exterior use.
- Highly flammable; Do not use near machinery, flame or spark source.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com