

Selleys Storm Clear (Tube)

Description

Storm™ Sealant with Sil-X™ technology delivers an immediate waterproof seal on any building material*, wet or dry, indoors or outdoors. It can even be applied in the rain to stop leaks in an instant.

Product Information

Packaging	Size	Colour
Tube	75g	Clear

Uses

- For sealing, bonding and filling
- Suitable for wet or dry surfaces
- For interior/exterior applications
- Suitable for use on glass, metal, timber, brick, concrete, tiles and most plastics#

Technical Features

- Waterproof
- Weather resistant
- Highly flexible
- For indoor & outdoor
- Paintable
- UV resistant
- Low odour
- Stops & prevents leaks

Technical Details

Property	Typical Result
Technology	Moisture curing silyl-modified polymer (SMP)
Colour	Clear
Density	~1.04 g/ml
Application Temperature	5 to 35°C
Skin Time (23°C, 50% R.H.)	20 minutes
Tack Time (ASTM C 679)	60 minutes
Cure Rate (23°C, 50% R.H.)	3 to 4mm/24hrs
Slump	0mm
Tensile Strength (ASTM D 412)	1.5 MPa
Shore A Hardness	25 ± 5
Elongation at Break (ASTM D 412)	300%
Movement Capability (ASTM C 719)	± 12.5%
Service Temperature	0 to 70°C
Indicative data only, not intended for preparation of specifications	

Surface Preparation

Ensure surface is clean, dry and free from dust, grease, loose particles and old or crumbling sealant.

Directions for Use

- Using reverse end of cap, pierce seal & rotate to ensure orifice is fully open. Fit turnkey at bottom of tube.
- Apply directly from tube for easier application – use nozzle only for fine applications. Turn key to apply.
- Ensure product is forced into joint with good contact to surfaces. Smooth off with tool tipped in turps or white spirits within 5 minutes of applying.
- Replace cap tightly immediately after use. Store in a dry cool place. After opening sealant should be used within 3 months.
- If painting, paint with two coats of quality water-based exterior paint.

Tips

- For neater joints, mask sides before applying sealant and remove tape before sealant skins.
- Forms an instant seal but must not be disturbed until cured (~48hours).
- Paint with water-based exterior paint.
- If paint does not wet out sealant surface properly, lightly sand sealant before painting.

Clean Up

- Clean up with turps before sealant cures.
- Cured sealant can be removed by scraping or sanding.

Storage

Store in cool, dry conditions below 30°C. Use within 3 months of opening.

Limitations

- Cannot be painted with solvent based paints. If required, paint with a water-based paint first.
- #Not for Polyethylene, Polypropylene or PTFE,
- Not for permanent water immersion or plugging leaks subject to pressure.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com