

Selleys Supa Glue Shock Proof

Description

SELLEYS Supa Glue Shock Proof is a breakthrough in Supa Glue technology. It has superior bond strength on metal. It is impact resistant, heat resistant up to 150 c and is more flexible than standard super glues. Shock Proof has been formulated to give you more working time than standard Super Glues and sets in around 2-3 minutes. And of course you know that if it's Selleys it works!

Product Information

Packaging	Size	Colour
Tube	3 mL	Clear

Uses

Supa Glue Shock Proof is ideal for small repair jobs or when immediate results are required. Ideal to bond surfaces such as ceramic, china, paper, metal, wood, and most plastics**.

Features

- Impact and heat resistant*
- Superior Strength
- Shock Proof: 3x more shock resistant than standard cyanoacrylate glues
- Heat resistant
- Fast setting
- Dries clear
- Water resistant
- No mixing required

Technical Details

Property	Typical Result
Technology	Cyanoacrylate glue
Colour	Clear
Density	1.07
Setting Time	3 minutes
Max Bond Time	24 hours
Tensile Strength ASTM D-2095 Steel-to-steel	10-20 N/mm ²
Tensile Shear Strength ASTM D-2002 Steel-to-steel	10-20 N/mm ²
Service Temperature	-55°C to 105°C
Indicative data only, not intended for preparation of specifications	

Surface Preparation

The surfaces to be bonded should be clean, dry and free of grease.

Directions for Use

- Pierce seal at the end of the tube by attaching nozzle and cap and turning clockwise.
- Remove cap and apply a small amount of glue to one surface. Bring surfaces together and apply slight pressure.
- Sufficient bond strength for practical use achieved after 12 hours. Bond will strengthen over 48 hours.
- Wipe tip of tube, replace cap and store upright in a dry cool place.

Clean Up

Uncured product may be removed with acetone. Cured product can be sanded and scraped.

Storage

Store in cool and dry place, out of direct sunlight.

Limitations

- May cause some leather to discolour or harden – pre-test on an inconspicuous area.
- **Not for polyethylene, polypropylene plastics. Use Selleys™ All Plastic Fix.
- Not for glass.
- Not suitable for continuous exposure to elevated temperature

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com